

Overview

EDPM gasket designed to maintain continuous air barrier integrity at pipe penetrations through below slab, exterior walls and ceiling air barrier membranes. The gasket stretches to form a tight, durable seal around single wire penetrations with diameter up to 1/2" providing a consistent, code-compliant alternative to site applied sealants. Reduces installation time, variability and long-term air leakage risk. Suitable for new construction and retrofit applications where airtightness performance is critical.

Features & Benefits

- Fast and Effective Air-tightness solution
- Sized for Elec wires up to 1/2" in diameter
- Faster install, long term performance
- Improves overall air-tightness

Applications

- Underslab pipe penetrations (plumbing/conduits)
- Exterior wall penetrations (vents/exhaust/conduits hose bibbs/irrigation/wires/gas lines)
- Ceiling air barrier penetrations (vents/conduits)

Specifications

Property	Value
Material	EPDM
Thickness / Gauge	45 mil (1.2 mm) +/- 10%
Dimensions	6" x 6" (15.2cm x 15.2cm)
Weight	1.34 ounce (38 grams)
Temperature Range	-40°F to 200°F (-40°C to 100°C)
Packaging	Individual piece, box of 50, box of 100
Storage / Handling	Store between 40°F and 100°F (4°C and 37°C)



Key Identifiers

- SKU / Part No.: ABE6SGL
- UPC: 628774587062
- Color: Black
-  Installation Page
-  Installation Video

Project: _____
Date: _____

Contractor Reviewed: _____
Architect Reviewed: _____